




Resmon™ Pro

Forced Oscillation Technique

RESMON PRO



Not approved for
clinical or diagnostic
use in the U.S.A.



The Resmon Pro is a professional, stand-alone device for non-invasively diagnosing and evaluating pulmonary diseases. Technologists love the Resmon Pro because it is accurate, versatile and efficient. Patients love it because it is fast and easy to use.

The Resmon Pro uses the forced oscillation technique (FOT) to measure the mechanical properties of the lung and airways. FOT is unique because it assesses the respiratory system's response to small-pressure stimuli applied to the opening of the airway during normal breathing.

With just a few normal tidal breaths from the patient, the Resmon Pro can do its job—identifying standard breathing patterns, detecting expiratory flow limitation (EFL), assessing airway obstructions, and evaluating bronchial reversibility and bronchial challenge. The Resmon Pro is an essential diagnostic tool for measuring respiratory function in individuals who cannot perform spirometry—including elderly or pediatric patients and patients with neuromuscular disease.

With such versatility, the Resmon Pro is ideal for virtually any testing environment—including laboratories, private offices, industrial settings, and sites for clinical trials or research studies.

The Resmon Pro requires no personal computer and is a complete stand-alone system for evaluating pulmonary function. It includes:

- A wide touchscreen for fast, easy and intuitive test management
- Several built-in measurement protocols, including
 - Classical pseudorandom noise (5–37 Hz)
 - Within-breath single (5, 6, 8, 10 Hz) frequency
 - Innovative within-breath multiple (5 + 11 + 19 Hz) frequency
- Built-in database to store and retrieve patient data
- Multi-user access with data security
- Detailed report of results
- Connectivity options



TECHNICAL DATA

FLOW MEASUREMENT	Range: ± 2 L/s Resistance: $0.4 \text{ cm H}_2\text{O/L/s}^{-1}$
MOUTH PRESSURE	Range: $\pm 25.5 \text{ cm H}_2\text{O}$
TEST SIGNALS	Within-breath protocols: Single (5, 6, 8, 10 Hz); multiple (5 + 11 + 19 Hz) Pseudorandom noise (PRN): Multiple 5-37 Hz
CALIBRATION	Factory calibration according to international guidelines + auto-zeroing of the sensors before each test + calibration check with a test object (provided) for both resistance and reactance

FOT PARAMETERS

Within-breath analysis	Single/multiple frequency	R_{insp} : Mean inspiratory resistance R_{exp} : Mean expiratory resistance R_{tot} : Mean resistance X_{insp} : Mean inspiratory reactance X_{exp} : Mean expiratory reactance X_{tot} : Mean reactance
	EFL index	ΔX_{rs} for detection of expiratory flow limitation
	Heterogeneity index	R_{5-19} : Degree of heterogeneity of airway obstruction
	PRN	Resistance and reactance frequency spectra f_{res} : Frequency of resonance R_0 : Resistance at the breathing frequency

BREATHING PATTERN	T_i : Inspiratory time T_e : Expiratory time T_i/T_{tot} : Respiratory duty cycle	V_t : Tidal volume V_t/T_i : Mean inspiratory flow V_t/T_e : Mean expiratory flow	RR: Respiratory rate
-------------------	--	---	----------------------

CONNECTIVITY 2 USB ports for external peripherals
 Ethernet 10/100, GPRS modem, 56k analog modem (optional)
Bluetooth[®] wireless technology module (optional) to communicate with external devices (e.g., pulse oximeter, ECGs)

PROCESSOR AND MEMORY Dual core architecture, 64 MB RAM, 4 GB flash memory

DISPLAY 5.7" LCD backlit touchscreen display

ELECTRICAL SPECIFICATIONS 100/240 V, 50/60 Hz 60 W input AC/15 VDC output power supply (included)

CERTIFICATION MDD 93/42 EEC

MGC DIAGNOSTICS CORPORATION, manufactured by RESTECH, distributed exclusively by Medical Graphics Corporation
 350 Oak Grove Parkway St. Paul, Minnesota USA 55127-8599

© 2012 MGC Diagnostics Corporation or one of its affiliates. All rights reserved.

All specifications subject to change without notice. Products may vary from those illustrated.

MGC Diagnostics Corporation and its affiliates are equal opportunity/affirmative action employers committed to cultural diversity in the workforce.

Part# 060120-001 RevA

